



RIGIDFLOOR® INFORMATION

RIGIDFLOOR, Roseburg's premium grade plywood flooring underlayment, is manufactured to out perform all other underlayment panels on the market today. Installed over RFPI-Joists at 24" o.c., RIGIDFLOOR meets APA's Code Plus® Floor criteria.

CUSTOMER BENEFITS

- Superior, high performance RIGIDFLOOR component is designed to enhance I-Joist floor systems.
- High strength and stiffness characteristics, resulting in a solid feel – reduces spring and bounce in floor system.
- Reduces material and installation costs while providing superior performance.
- Rated for support spacing up to 32" o.c.
- Face is Douglas Fir veneer sanded to a smooth finish

RIGIDFLOOR is an Exposure 1 rated panel, produced with a fully exterior adhesive. Veneers are all Group 1 species. B equivalent faces with maximum 3/4" open defect in crossband under face. Innerplies C grade maximum open defects. C grade backs. Meets or exceeds PS1-95.

QUICK ENGINEERING SPECS.

SPAN RATING	32" o.c.
PANEL SIZE	48" x 96" 7/8" thick
CONSTRUCTION	7-Ply, all Group 1, Exposure 1 plywood
EDGE TREATMENT	T&G on both long edges (2LE), coated with red edge sealer

