

PLYWOOD, LAMINATED VENEER LUMBER, PRE-FABRICATED I-JOIST AND PARTICLEBOARD LABEL FOR WOOD DUST AND FORMALDEHYDE RELEASE

Wood Dust (from sawing, sanding or machining wood products) and possible release of small quantities of formaldehyde vapor.

WARNING

Sawing, sanding, or machining wood products can produce wood dust that can cause a flammable or explosive hazard.

Inhalation and skin contact may cause dermatitis and increased risk of upper respiratory tract disease. Wood dust can cause mechanical irritation of the respiratory tract. Some species of wood and formaldehyde may cause allergic contact dermatitis and respiratory allergies in sensitized persons. Formaldehyde and wood dust are related to respiratory tract cancers.

- Avoid repeated or prolonged breathing of wood dust.
- Saw, sand or machine wood products using adequate ventilation.
- Wear gloves to reduce skin contact.
- Wear eye protection when sawing, sanding or machining the product.
- **Wood dust is combustible.** Avoid ignition sources. If product is heated, it can release toxic thermal decomposition products.

FIRST AID:

- **Eye contact.** Flush eyes with large amounts of water. If irritation persists or allergic response occurs, seek medical attention.
- **Skin Contact.** Prolonged and repeated contact with skin: Use proper personal hygiene and wash with soap and water. Get medical advice if rash or persistent irritation.
- **Inhalation.** Remove to fresh air. Get medical advice if persistent irritation, severe coughing or breathing difficulty occurs.

**FOR ADDITIONAL INFORMATION
SEE MATERIAL SAFETY DATA SHEET (MSDS)**